



## Agile L2 Access Switch Solution for Converged Data, Video and Voice Networking

- Fully managed Layer 2 switching solution
- High power budget of 375 W (24HP/28HP/48HP/52HP) and 180 W (8HP)
- L2 multicast, IGMP snooping, MVR and voice VLAN for convergence
- Enhanced network protection with IP source guard, DHCP snooping, ARP inspection, CPU protection
- L2, L3 and L4 filtering, MAC freeze, port isolation, guest VLAN for improved isolation and access control
- Limited life-time warranty\*
- ZyXEL One Network is supported

\* Warranty terms, service availability, and service response times may vary from country or region to country or region.



ZyXEL **onenetwork**  
Redefining network integration

**XGS2210/GS2210 Series**  
8/24/28/48/52-port GbE L2 Switch

Incorporating data, video and voice communications into a single IP network provides more effective communications, centralized IT management, and lower overall deployment cost for the entire organization.

The ZyXEL XGS2210/GS2210 Series are fully featured Layer 2 Gigabit access switches designed to meet these converged data, video and voice networking needs. The Series comes in 8-, 24-, 28-, 48- and 52-port models with a combination of PoE and non-PoE, as well as Gigabit (GS2210 Series) and 10 Gigabit (XGS2210 Series) uplink options. The PoE models comply with the IEEE 802.3af PoE and 802.3at PoE Plus standards and provide a high PoE power budget. With rich traffic shaping, network isolation, and security features, the XGS2210/GS2210 Series is the perfect L2 access switch solution for converged data, video and voice networking.

### Benefits

#### Agile traffic control for converged networking applications

Designed for access layer converged data, video and voice applications, the ZyXEL XGS2210/GS2210 Series has a rich Layer 2 feature set that can shape the traffic for diverse VoIP, video conference, IPTV and IP surveillance deployments. Supporting L2 multicast and IGMP snooping, the XGS2210/GS2210 Series can support large IPTV deployments, while using bandwidth efficiently by directing multicast traffic to the subscribers only. The Multicast VLAN Registration (MVR) function ensures better network security by allowing a single multicast VLAN to be shared in the network while subscribers remain in separate VLANs. In terms of voice, the XGS2210/GS2210 switch uses OUI to detect compliant IP phones, and then assigns the delay-sensitive VoIP traffic to a dedicated voice VLAN with appropriate QoS prioritization. These advanced traffic control features of the XGS2210/GS2210 Series provide hotels, businesses and educational institutions greater agility and more effective traffic management for the converged applications of today.



ZON Utility



Power Cycle



Reset to Default



Web GUI Redirection



Neighbor Device Discovery

### ZyXEL One Network experience

Aiming for relieving our customers from repetitive operations of deploying and managing a network, ZyXEL One Network is designed to simplify the configuration, management, and troubleshooting, allowing our customers to focus on the business priorities. ZyXEL One Network presents an easy-to-use tool, ZyXEL One Network Utility (ZON Utility), to realize speed network setup. ZyXEL Smart Connect allows ZyXEL networking equipment to be aware and recognize each other and further facilitating the network maintenance via one-click remote functions such as factory reset or power cycling. ZyXEL One Network redefines the network integration across multiple networking products from switch to Wi-Fi AP and to Gateway.

### Intelligent and high-powered Power over Ethernet (PoE)

The ZyXEL XGS2210/GS2210 Series PoE switches feature advanced and intelligent PoE functions that simplify and lower the cost of PoE deployments such as IP telephony, WLAN and IP surveillance. This Series of L2 PoE switches support the IEEE 802.3af PoE and 802.3at PoE Plus standards, which provide up to 30 watts of power per port for advanced Powered Devices (PD) like 802.11ac wireless APs and video IP phones. The high power budget enables the XGS2210/GS2210 PoE switches to comfortably accommodate the PDs required in a modern network edge.

The intelligent PoE technology used in the XGS2210/GS2210 PoE switches can automatically detect the power requirements of each PoE device and supply only what is needed, minimizing overall power consumption while maximizing the number of devices the switch can power.

### High level network and access security

Equipped with an extensive array of access security, traffic security and network storm protection features, the ZyXEL XGS2210/GS2210 Series offers enhanced control and isolation for improved convergence of video, voice and data. Such advanced defense mechanisms as IP source guard, DHCP snooping, and ARP inspection can detect and block intentional network attacks. The CPU protection function ensures normal switch operation by preventing malicious traffic from trying to shut down the switch. Combining multiple L2, L3 and L4 filtering mechanisms with such education- and hospitality-friendly features as MAC freeze, port isolation and guest VLAN, the ZyXEL XGS2210/GS2210 Series offers a high level of security, flexibility and control for diverse access layer deployments.

### Future-proof connectivity for evolving networks

Full IPv6 support with features including auto-configuration, duplicate address prevention, dual-stack (IPv4 and IPv6) and neighbor discovery, the ZyXEL XGS2210/GS2210 Series helps businesses and organizations stay ahead and get ready for future IPv6 networks.



**Model List**

**XGS2210-52**  
48-port GbE L2 Switch with 10GbE Uplink



- 48 x GbE RJ-45 ports
- 4 x 10 GbE SFP+ ports

**XGS2210-52HP**  
48-port GbE L2 PoE Switch with 10GbE Uplink



- 48 x GbE PoE RJ-45 ports
- 4 x 10 GbE SFP+ ports
- PoE power budget: 375W

**XGS2210-28**  
24-port GbE L2 Switch with 10GbE Uplink



- 24 x GbE RJ-45 ports
- 4 x 10 GbE SFP+ ports

**XGS2210-28HP**  
24-port GbE L2 PoE Switch with 10GbE Uplink



- 24 x GbE PoE RJ-45 ports
- 4 x 10 GbE SFP+ ports
- PoE power budget: 375W

**GS2210-48**  
48-port GbE L2 Switch



- 44 x GbE RJ-45 ports
- 2 x GbE SFP ports
- 4 x GbE combo (RJ-45/SFP) ports

**GS2210-48HP**  
48-port GbE L2 PoE Switch



- 48 x GbE PoE RJ-45 ports
- 2 x GbE SFP ports
- 4 x GbE combo (RJ-45/SFP) ports
- PoE power budget: 375W

**GS2210-24**  
24-port GbE L2 Switch



- 24 x GbE RJ-45 ports
- 4 x GbE combo (RJ-45/SFP) ports

**GS2210-24HP**  
24-port GbE L2 PoE Switch



- 24 x GbE PoE RJ-45 ports
- 4 x GbE combo (RJ-45/SFP) ports
- PoE power budget: 375W

**GS2210-24LP**  
24-port GbE L2 Lite-PoE Switch



- 24 x GbE PoE RJ-45 ports
- 4 x GbE combo (RJ-45/SFP) ports
- PoE power budget: 180W

**GS2210-8HP**  
8-port GbE L2 PoE Switch



- 8 x GbE PoE RJ-45 ports
- 2 x GbE combo (RJ-45/SFP) ports
- PoE power budget: 180W

**GS2210-8**  
8-port GbE L2 Switch




- 8 x GbE RJ-45 ports
- 2 x GbE combo (RJ-45/SFP) ports

### Key Applications


#### IPTV, surveillance and guest access (hospitality)

- Each guest room can be assigned a dedicated data VLAN to provide better isolation and security to the Internet users
- The MVR function allows a single IPTV multicast VLAN to be shared with all the set-top boxes while the subscribers remain in separate data VLANs
- The total PoE power budget of up to 375 watts provides full supports to wireless APs and IP surveillance devices. (24HP/28HP/48HP/52HP)
- Enabling the IGMP snooping function allows IPTV traffic to be directed to the subscribers only, which reduces the waste of bandwidth caused by multicasting IPTV traffic to all ports
- The rich QoS feature set provides effective bandwidth prioritization and control to ensure various services quality and prevent bandwidth abuse







#### Robust network infrastructure (education)

- The high power budget makes the XGS2210/GS2210 Series perfect for classroom WLAN deployments with many APs for student digital textbooks
- The XGS2210/GS2210 Series switch can separate the teacher's network from the student's network and grant different bandwidth privileges with port-based and ACL-based bandwidth management
- Support for 8 hardware queues per port and QoS based on 802.1p and DSCP reduces traffic congestions for latency-sensitive interactive learning applications
- Advanced defense mechanisms like IP source guard, DHCP snooping and ARP inspection safeguards the network from intentional attacks








### Specifications

Model	XGS2210-52	XGS2210-52HP	XGS2210-28	XGS2210-28HP	
<b>Product name</b>	48-port GbE L2 Switch with 10GbE Uplink 	48-port GbE L2 PoE Switch with 10GbE Uplink 	24-port GbE L2 Switch with 10GbE Uplink 	24-port GbE L2 PoE Switch with 10GbE Uplink 	
<b>Switch class</b>	Layer 2	Layer 2	Layer 2	Layer 2	
<b>Port Density</b>					
<b>Total port count</b>	52	52	28	28	
<b>100/1000 Mbps</b>	48	-	24	-	
<b>100/1000 Mbps PoE</b>	-	48	-	24	
<b>10 Gigabit SFP+</b>	4	4	4	4	
<b>Gigabit SFP</b>	-	-	-	-	
<b>Gigabit combo (SFP/RJ-45)</b>	-	-	-	-	
<b>Performance</b>					
<b>Switching capacity (Gbps)</b>	176	176	128	128	
<b>Forwarding rate (Mpps)</b>	130.9	130.9	95.2	95.2	
<b>Packet buffer (byte)</b>	1.5 M	1.5 M	1.5 M	1.5 M	
<b>MAC address table</b>	16 K	16 K	16 K	16 K	
<b>L3 forwarding table</b>	Max. 1 K IPv4 entries; Max. 512 IPv6 entries				
<b>Static route</b>	64				
<b>IP interface</b>	32				
<b>Power</b>					
<b>Input</b>	100 - 240 V AC, 50/60 Hz				
<b>Max. power consumption (watt)</b>	45	495	20	453	
<b>Total PoE power budget (watt)</b>	-	375	-	375	
<b>Physical Specifications</b>					
<b>Item</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	441 x 270 x 45/ 17.36 x 10.63 x 1.77	440 x 330 x 44.5/ 17.32 x 12.99 x 1.75	441 x 270 x 45/ 17.36 x 10.63 x 1.77	440 x 330 x 44.5/ 17.32 x 12.99 x 1.75
	<b>Weight (kg/lb.)</b>	3.86/8.51	5.38/11.86	3.7/8.16	5.06/11.16
<b>Packing</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	622 x 358 x 108/ 24.49 x 14.09 x 4.25	586 x 452 x 97/ 23.07 x 17.8 x 3.82	622 x 358 x 108/ 24.49 x 14.09 x 4.25	586 x 452 x 97/ 23.07 x 17.8 x 3.82
	<b>Weight (kg/lb.)</b>	4.92/10.85	6.75/14.9	4.8/10.58	6.4/14.1
<b>Included accessories</b>	• Power cord • Rack mounting kit				
<b>Green Feature</b>					
<b>Fanless</b>	-	-	Yes	-	
<b>Environmental Specifications</b>					
<b>Operating</b>	<b>Temperature</b>	0°C to 50°C/32°F to 122°F			
	<b>Humidity</b>	10% to 95% (non-condensing)			
<b>Storage</b>	<b>Temperature</b>	-40°C to 70°C/-40°F to 158°F			
	<b>Humidity</b>	10% to 90% (non-condensing)			
<b>MTBF (hr)</b>	970,594	500,904	831,699	560,726	
<b>Heat dissipation (BTU/hr)</b>	153.3	1,688	68.2	1,483.4	
<b>Acoustic noise (dBA)</b>	51.6	57.6	0	57	





## XGS2210/GS2210 Series

8/24/28/48/52-port GbE L2 Switch

Model	GS2210-48	GS2210-48HP	GS2210-24	GS2210-24HP	GS2210-24LP	
<b>Product name</b>	48-port GbE L2 Switch 	48-port GbE L2 PoE Switch 	24-port GbE L2 Switch 	24-port GbE L2 PoE Switch 	24-port GbE L2 Lite-PoE Switch 	
<b>Switch class</b>	Layer 2	Layer 2	Layer 2	Layer 2	Layer 2	
<b>Port Density</b>						
<b>Total port count</b>	50	50	28	28	28	
<b>100/1000 Mbps</b>	44	-	24	-	-	
<b>100/1000 Mbps PoE</b>	-	48	-	24	24	
<b>Gigabit SFP</b>	2	2	-	-	-	
<b>Gigabit combo (SFP/RJ-45)</b>	4	4	4	4	4	
<b>Performance</b>						
<b>Switching capacity (Gbps)</b>	100	100	56	56	56	
<b>Forwarding rate (Mpps)</b>	74	74	41.67	41.67	41.67	
<b>Packet buffer (byte)</b>	1.5 M	1.5 M	1.5 M	1.5 M	1.5 M	
<b>MAC address table</b>	16 K	16 K	16 K	16 K	16 K	
<b>Power</b>						
<b>Input</b>	100 - 240 V AC, 50/60 Hz					
<b>Max. power consumption (watt)</b>	40	461	27.2	476.7	253.4	
<b>Total PoE power budget (watt)</b>	-	375	-	375	180	
<b>Physical Specifications</b>						
<b>Item</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	440 x 200 x 44.5/ 17.32 x 7.87 x 1.75	440 x 330 x 44.5/ 17.32 x 12.99 x 1.75	441 x 131 x 44/ 17.36 x 5.16 x 1.73	440 x 330 x 44.5/ 17.32 x 12.99 x 1.75	440 x 330 x 44.5/ 17.32 x 12.99 x 1.75
	<b>Weight(kg/lb.)</b>	3.04/6.7	5.13/11.3	2.62/5.78	4.79/10.56	4.40/9.7
<b>Packing</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	512 x 293 x 92/ 20.15 x 11.53 x 3.62	586 x 452 x 97/ 23.06 x 17.79 x 3.82	561 x 220 x 82/ 22.08 x 8.66 x 3.23	583 x 451 x 98/ 22.95 x 17.75 x 3.86	583 x 451 x 98/ 22.95 x 17.75 x 3.86
	<b>Weight (kg/lb.)</b>	4.10/9.06	6.25/13.81	3.41/7.54	5.90/13.03	5.58/12.3
<b>Included accessories</b>	<ul style="list-style-type: none"> <li>• Power cord</li> <li>• Rack mounting kit</li> </ul>					
<b>Green Feature</b>						
<b>Fanless</b>	-	-	Yes	-	-	
<b>Environmental Specifications</b>						
<b>Operating</b>	<b>Temperature</b>	0°C to 50°C/32°F to 122°F				
	<b>Humidity</b>	10% to 95% (non-condensing)				
<b>Storage</b>	<b>Temperature</b>	-40°C to 70°C/-40°F to 158°F				
	<b>Humidity</b>	10% to 90% (non-condensing)				
<b>MTBF (hr)</b>	631,451	337,690	616,247	949,326	616,247.3	
<b>Heat dissipation (BTU/hr)</b>	136.8	1,572.01	92.75	1,625.55	864.094	
<b>Acoustic noise (dBA)</b>	40.9	43.6	0	59.6	54	



**XGS2210/GS2210 Series**  
8/24/28/48/52-port GbE L2 Switch

Model		GS2210-8	GS2210-8HP
<b>Product name</b>		8-port GbE L2 Switch 	8-port GbE L2 PoE Switch 
<b>Switch class</b>		Layer 2	Layer 2
<b>Port Density</b>			
<b>Total port count</b>		10	10
<b>100/1000 Mbps</b>		8	-
<b>100/1000 Mbps PoE</b>		-	8
<b>Gigabit SFP</b>		-	-
<b>Gigabit combo (SFP/RJ-45)</b>		2	2
<b>Performance</b>			
<b>Switching capacity (Gbps)</b>		20	20
<b>Forwarding rate (Mpps)</b>		15	15
<b>Packet buffer (byte)</b>		1.5 M	1.5 M
<b>MAC address table</b>		16 K	16 K
<b>Power</b>			
<b>Input</b>		100 - 240 V AC, 50/60 Hz	
<b>Max. power consumption (watt)</b>		12.3	230
<b>Total PoE power budget (watt)</b>		-	180
<b>Physical Specifications</b>			
<b>Item</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	250 x 150 x 44/ 9.84 x 5.91 x 1.73	330 x 230.5 x 44.5/ 12.99 x 9.07 x 1.75
	<b>Weight(kg/lb.)</b>	1.425/3.14	2.703/5.96
<b>Packing</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	366 x 214 x 79/ 14.41 x 8.43 x 3.11	389 x 337 x 79/ 15.31 x 13.27 x 3.11
	<b>Weight (kg/lb.)</b>	2.27/5	3.65/8.05
<b>Included accessories</b>		<ul style="list-style-type: none"> <li>• Power cord</li> <li>• Wall mount kit</li> <li>• Rack mounting kit</li> </ul>	<ul style="list-style-type: none"> <li>• Power cord</li> <li>• Rack mounting kit</li> </ul>
<b>Green Feature</b>			
<b>Fanless</b>		Yes	-
<b>Environmental Specifications</b>			
<b>Operating</b>	<b>Temperature</b>	0°C to 50°C/32°F to 122°F	
	<b>Humidity</b>	10% to 95% (non-condensing)	
<b>Storage</b>	<b>Temperature</b>	-40°C to 70°C/-40°F to 158°F	
	<b>Humidity</b>	10% to 90% (non-condensing)	
<b>MTBF (hr)</b>		1,382,030	1,155,719
<b>Heat dissipation (BTU/hr)</b>		41.94	784.30
<b>Acoustic noise (dBA)</b>		0	37.7

## Features

### Standard Compliance

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Ethernet
- IEEE 802.3ab 1000BASE-T Ethernet
- IEEE 802.3z 1000BASE-X
- IEEE 802.3af PoE
- IEEE 802.3at PoE plus
- IEEE 802.3az EEE
- IEEE 802.3x flow control
- IEEE 802.3ad LACP aggregation
- IEEE 802.1AB LLDP/LLDP-MED
- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- IEEE 802.1Q VLAN tagging
- IEEE 802.1p Class of Service (CoS) prioritization
- IEEE 802.1X port authentication

### Resilience and Availability

- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- IEEE 802.3ad LACP
- Loop guard
- **New** Root guard
- **New** BPDU guard
- ErrDisable recovery
- MRSTP (ZyXEL Proprietary)
- Dual configuration files
- Dual images

### Traffic Control

- 802.1Q static VLANs/dynamic VLANs: 1 K/4 K
- Port-based VLAN
- Protocol-based VLAN
- IP subnet-based VLAN
- MAC-based VLAN
- Private VLAN
- Voice VLAN
- VLAN ingress filtering
- LACP algorithm of source/destination IP or MAC
- GVRP
- L2PT

### Security

- 802.1X
- Port security
- Layer 2 MAC filtering
- Layer 3 IP filtering
- Layer 4 TCP/UDP socket filtering
- Static MAC forwarding
- Multiple RADIUS servers
- Multiple TACACS+ servers
- 802.1x VLAN and 802.1p assignment by RADIUS
- Login authentication by RADIUS
- Login authentication by TACACS+
- TACACS+ accounting
- Authorization on RADIUS
- Authorization on TACACS+
- SSH v1/v2
- SSL
- Intrusion lock
- MAC freeze
- DHCP snooping
- ARP inspection
- Static IP-MAC-Port binding
- Policy-based security filtering
- Port isolation
- **New** IP source guard (IPv4/IPv6)
- MAC search
- Guest VLAN
- ACL packet filtering (IPv4/IPv6)
- CPU protection
- Interface related trap enable/disable (by port)
- **New** MAC-based authentication per VLAN

### Quality of Service (QoS)

- No. of hardware queues per port: 8
- Storm control: Broadcast, multicast, unknown unicast (DLF)
- Port-based rate limiting (ingress/egress)
- Rate limiting per IP/TCP/UDP per port
- Policy-based rate limiting
- 802.3x flow control
- 802.1p Class of Service (SPQ, WFQ, WRR, hybrid-SPQ combination capable)
- DiffServ (DSCP)

### Layer 2 Multicast

- L2 multicast
- IGMP snooping (v1, v2, v3)
- IGMP snooping fast leave
- Configurable IGMP snooping timer and priority
- IGMP snooping statistics
- IGMP throttling
- MVR support
- IGMP filtering
- IGMP snooping immediate leave
- IGMP proxy mode & snooping mode selection
- MLD snooping

### Routing

#### (XGS2210 Series only)

- Static route
- IP port moving

### Manageability

- SNMP v1, v2c, v3
- SNMP trap group
- RMON (1, 2, 3, 9)
- ICMP echo/echo reply
- Syslog
- IEEE 802.1AB LLDP
- IEEE 802.1AB LLDP-MED

### IPv6 Management

- IPv6 over Ethernet (RFC 2464)
- IPv6 addressing architecture (RFC 4291)
- Dual stack (RFC 4213)
- ICMPv6 (RFC 4443)
- Path MTU (RFC 1981)
- Minimum path MTU size of 1280 (RFC 5095)
- Encapsulation for maximum PMTU of 1500
- Neighbor discovery (RFC 4861)
- DHCPv6 relay
- **New** Default DHCP client mode

### Device Management

- ZyXEL iStacking™
- Web interface
- Management through Console, Telnet, SNMP
- Remote firmware upgrade by FTP/Web/TFTP



- Configuration saving and retrieving
- Multiple logins supported
- Configure clone
- Multilevel CLI
- CLI (Cisco-like)
- DHCP relay per VLAN
- DHCP client
- DHCP option 82
- Daylight saving
- NTP
- Port mirroring
- RS-232 out-of-band console port
- **New** Scheduled PoE
- sFlow (XGS2210 series only)

### MIB

- ZyXEL new private MIB
- RFC 1066 TCP/IP-based MIB
- RFC 1213, 1157 SNMPv2c/v3 MIB
- RFC 1493 bridge MIB
- RFC 1643 Ethernet MIB
- RFC 1757 RMON group 1, 2, 3, 9
- RFC 2011, 2012, 2013 SNMPv2 MIB
- RFC 2233 SMIv2 MIB

- RFC 2358 Ethernet-like MIB
- RFC 2674 bridge MIB extension
- RFC 2819, 2925 remote management MIB
- RFC 3621 power Ethernet MIB
- RFC 4022 management information base for transmission control protocol
- RFC 4113 management information base for user datagram protocol
- RFC 4292 IP forwarding table MIB
- RFC 4293 Management Information Base (MIB) for IP

### Certifications

#### Safety

- LVD
- BSMI

#### EMC

- FCC Part 15 (Class A)
- CE EMC (Class A)
- BSMI EMC

#### RoHS

- Level A

### ZyXEL One Network

#### ZON Utility

- Discovery of ZyXEL switches, APs and gateways
- Centralized and batch configurations
  - IP configuration
  - IP renew
  - **New** Device factory reset
  - Device reboot
  - Device locating
  - Web GUI access
  - Password configuration
  - One-click quick association with ZyXEL AP Configurator (ZAC)

#### Smart Connect

- Discover neighboring devices
- One-click remote management access to the neighboring ZyXEL devices
- Reset neighboring devices remotely to factory defaults
- Power cycle neighboring powered devices (PoE switches only)

## Accessories

### Transceivers (Optional)

Model	Speed	Connector	Wavelength	Max. Distance	DDMI
<b>SFP10G-SR</b>	10-Gigabit SFP+	Duplex LC	850 nm	300 m (984 ft)	Yes
<b>SFP10G-LR</b>	10-Gigabit SFP+	Duplex LC	1310 nm	10 km (10936 yd)	Yes
<b>SFP-1000T</b>	Gigabit	RJ-45	-	100 m (109 yd)	-
<b>SFP-BX1310-10-D</b>	Gigabit	LC	1310 nm (Tx); 1490 nm (Rx)	10 km (10936 yd)	Yes
<b>SFP-BX1490-10-D</b>	Gigabit	LC	1490 nm (Tx); 1310 nm (Rx)	10 km (10936 yd)	Yes
<b>SFP-LHX1310-40-D</b>	Gigabit	LC	1310 nm	40 km (43744 yd)	Yes
<b>SFP-LX-10-D</b>	Gigabit	LC	1310 nm	10 km (10936 yd)	Yes
<b>SFP-SX-D</b>	Gigabit	LC	850 nm	550 m (601 yd)	Yes
<b>SFP-ZX-80-D</b>	Gigabit	LC	1550 nm	80 km (87488 yd)	Yes
<b>SFP-100BX1310-20-D</b>	Fast Ethernet	LC	1310 nm (Tx); 1550 nm (Rx)	20 km (21872 yd)	Yes
<b>SFP-100BX1550-20-D</b>	Fast Ethernet	LC	1550 nm (Tx); 1310 nm (Rx)	20 km (21872 yd)	Yes
<b>SFP-100FX-2</b>	Fast Ethernet	LC	1310 nm	2 km (2187 yd)	-
<b>SFP-100LX-20</b>	Fast Ethernet	LC	1310 nm	20 km (21872 yd)	-

### Direct Attach Cables (Optional)

Model	Connector	Cable Length
<b>DAC10G-1M</b>	SFP+ to SFP+	1 m (39.37 inch)
<b>DAC10G-3M</b>	SFP+ to SFP+	3 m (118.11 inch)



**XGS2210/GS2210 Series**  
8/24/28/48/52-port GbE L2 Switch





For more product information, visit us on the web at [www.ZyXEL.com](http://www.ZyXEL.com)



Copyright © 2016 ZyXEL Communications Corp. All rights reserved. ZyXEL, ZyXEL logo are registered trademarks of ZyXEL Communications Corp. All other brands, product names, or trademarks mentioned are the property of their respective owners. All specifications are subject to change without notice.

