

Wireless	
Standards	IEEE 802.11b/g/n 2.4GHz
Signal Rate	Up to 300Mbps 2.4GHz
Frequency Range	2.4-2.4835GHz;
Transmit Power	20dBm(MAX)
Data Transfer Rate	802.11n:  40MHz (300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps)  20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense)  802.11g:  (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps)  802.11b:  (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	AP/APR, Multi-SSID
Wireless Security	None / WEP / WPA-PSK/WPA2-PSK (TKIP/AES)

4G LTE	
Band for LTE	FDD-LTE:B1/B3/B5/B8 TDD-LTE: B38/B39/B40/B41 HSPA/UMTS:B1/B5/B8 GSM/GPRS/EDGE:B3/B8 TD-SCDMA:B34/B39 EVDO/CDMA:BC0
Mode	FDD-LTE, TDD-LTE, TD-SCDMA, HSPA+, HSUPA HSDPA, UMTS, EVDO, EDGE, GPRS, GSM, CDMA1x
Card Speed	FDD-LTE: 150 Mbps DL, 50 Mbps UL TDD-LTE: 132 Mbps DL, 30 Mbps UL TD-HSUPA:2.8Mbps DL TD-HSUPA:2.2Mbps UL DC-HSPA+:42 Mbps DL HSPA+:21 Mbps DL HSUPA:5.76Mbps UL WCDMA: 384 Kbps DL, 384Kbps UL CDMA2000 EVDO: 3.1Mbps DL, 1.8Mbps UL EDGE: 237 Kbps DL, 118Kbps UL

Hardware	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interface	1*10/100Mbps Auto MDI/MDIX RJ45 WAN port 2*10/100Mbps Auto MDI/MDIX RJ45 LAN port SIM card slot
LED Indicators	Power, LAN All, WiFi/WPS,EWAN, LTE Strong, LTE Middle, LTE Weak
Buttons	Default, WPS
Antenna	2* 5dBi WiFi antennas, 2 SMA detachable 4G antennas
Power Supply	DC 12V/1.0A(Output)
Dimensions (L x W x H )	182mm*108mm*25mm
WAN Type	WAN: DHCP / Static IP / PPPoE / Russia PPPoE / L2TP / PPTP / 3G&4G
Others	Bandwidth Control, Access Control, IPTV, Virtual Server, DMZ, VPN Pass-through, Dynamic DNS, Static Routing

Others	
Certification	FCC, CE, EAC
Environment	Operating Temperature: 0°C~40°C  Storage Temperature: -40°C~70°C  Operating Humidity: 10%~90% non-condensing  Storage Humidity: 5%~90% non-condensing
Package	1* MW5360  1* 12V/1A Power Adapter  1* Quick Installation Guide (Multilingual)