

| | |
|------------------------|---|
| Wireless | |
| Standards | IEEE 802.11b/g/n 2.4GHz IEEE 802.11a/n/ac 5GHz |
| Signal Rate | Up to 300Mbps 2.4GHz UP to 867Mbps 5GHz |
| Frequency Range | 2.4-2.4835GHz;5.180-5.825GHZ |
| Transmit Power | 20dBm(MAX) |
| Data Transfer Rate | 802.11ac: 80MHZ(433Mbps, 867Mbps) 802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps,9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps) |
| Wireless Modes | AP, Repeater, Client, Multi-SSID |
| Wireless Security | WEP/WPA-PSK/WPA2-PSK Encryption Wireless MAC Filtering |
| Hardware | |
| Standards | IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T |
| Interface | 1*10/100/1000Mbps Auto MDI/MDIX RJ45 WAN port 4*10/100/1000Mbps Auto MDI/MDIX RJ45 LAN port |
| LED Indicators | SYS, WPS, 5G, 2.4G, WAN, LAN1~LAN4 |
| Buttons | Default, WPS |
| Antenna | 4* external fixed 5dBi antenna |
| Power Supply | DC 12V/1.0A(Output) |
| Dimensions (L x W x H) | 212 x 145 x 40 mm |
| Software | |
| WAN Type | DHCP, Static IP, PPPoE, L2TP, PPTP, WISP |
| Others | Bandwidth Control, Access Control, IPTV, Virtual Server, DMZ, VPN Pass-through, Dynamic DNS, Static Routing, Backup & Restore |
| Others | |
| Certification | FCC, CE, EAC |
| Environment | Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing |
| Package | 1* N2 1* 12V/1.0A Power Adapter 1* Ethernet Cable 1* Quick Installation Guide (Multilingual) |