

netis®

Easy Network, Trustable

24 Port Gigabit Ethernet Rackmount Switch

ST3124GS



Features:

- >24 10/100/1000Mbps RJ45 ports
- >Supports MAC address self-learning and auto MDI/MDIX
- >Supports 16K MAC address table
- >48 Gbps Switching Capacity
- >3.5Mbit SDRAM Packet buffer
- >Fanless design to make sure it works quietly without disturbing your family
- >Standard 13-inch steel case
- >Plug and play, no configuration required

Brief:

The netis ST3124GS Gigabit Ethernet Rackmount Switch provides 24 10/100/1000Mbps Auto-Negotiation RJ45 ports. It is ideal for the small and medium office use. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or uplink ports. The 24 Port Gigabit Ethernet Rackmount Switch provides you with high-performance, seamless and standard upgrade to improve your old network to a 1000Mbps network.

Specification:

Hardware

| | |
|-------------------------|---|
| Interface | 24 * 10/100/1000Mbps RJ45 port, Auto-Negotiation, Auto MDI/MDIX |
| LED | PWR, LAN1-LAN24 |
| Power Supply | 100-240 V AC/50-60Hz |
| Dimensions (L x W x H) | 280 x 173 x 44 mm |

Switching Features

| | |
|---------------------------|--|
| Standard | IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000BASE-T , IEEE 802.3x Flow Control, IEEE 802.3az |
| Access Method | CSMA/CD |
| Transmission Method | Store and Forward |
| Data Transmission Rate | 10/100Mbps(Half-duplex) 20/200Mbps(Full-duplex) |
| Switching Fabric Capacity | 48Gbps |
| Built-in Buffer | 3.5M bits |
| Jumbo Frame | 9KB |
| MAC Address Table | 16K, auto-learning & auto-aging |

Others

| | | | |
|---------------|--|---|-----------------------------|
| Certification | FCC, CE | | |
| Environment | Operating Temperature: 0°C~40°C | Storage Temperature: -40°C~70°C | |
| | Operating Humidity: 10%~90% non-condensing | Storage Humidity: 5%~90% non-condensing | |
| Package | 1 * ST3124GS | 1 * Quick Installation Guide | 2 * Brackets 1 * Power Cord |