

## ХАРДУЕРНИ ХАРАКТЕРИСТИКИ

Интерфейс	1 10/100/1000Mbps RJ45 Data IN Port 1 10/100/1000Mbps RJ45 Passive PoE Port (24V) 1 220V AC POWER INPUT PORT
Мрежова медия	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Захранване	12W (Max. 24VDC)
LED индикатор	PWR
Размери (Ш x Д x В)	3.4*1.7*1.4 in.( 85.8mm*43.9mm*35mm)
<b>ДРУГИ</b>	
Сертификати	FCC, CE, RoHS
Съдържание на пакета	24V 12W Passive PoE Adapter TL-POE2412G Power Cord Wall Mounting Kits
Околна среда	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing